

## Dynamic GT BT

Manufacturing process	Needlefelt	ISO 2424					
Type of surface	Flecked						
Surface aspect	Coarse Fibred	ISO 2424					
Width	50*50 cm						
Backing	BT	ISO 2424					
Fibre composition	70% doricx® PA / 20% PES / 10% PP						
Total fibre weight of use surface	500 gr/m <sup>2</sup>						
Total weight	4200 gr/m <sup>2</sup>	+/- 15% ISO 8543					
Total height	6,5 mm	+15% / -10% ISO 1765					
Overall use class	Commercial 33, Areas with heavy use	EN ISO 10874					
Luxury class	LC1	EN 1307					
Castor chair suitability	Yes, permanent use	EN 985					
Stair suitability	No	EN 1307					
Colour fastness to light	≥ 5	ISO 105-B02					
Colour fastness to rubbing, wet and dry	≥ 4	ISO 105-X12					
Colour fastness to water	≥ 4	ISO 105-E01					
Colour fastness to soiling	≥ 3	EN 1269					
Electrostatic charging	< 2 kV	ISO 6356					
Vertical resistance	Ω	ISO 10965					
Horizontal resistance	Ω	ISO 10965					
Impact sound protection ΔLW	20 dB	ISO 10140					
Acoustical sound absorption α <sub>S</sub>	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	ISO 354
	0,00 αW	0,03 αW	0,06 αW	0,13 αW	0,30 αW	0,31 αW	
Evaluated sound absorptions grade α <sub>W</sub>	0,15	ISO 11654					
Thermal resistance	0,07 m <sup>2</sup> K/W (0,7 TOG)	ISO 8302					
Slip resistance	DS (> 0,30)	EN 13893					
Flammability	Bfl,s1	EN 13501-1					
Prodis-ID (GuT)	AC22A000	www.pro-dis.info					
TÜV PROFICERT product	Certificate number: 70-710-5617-4						

## Floorsymbols



## Certificates

EN 14041



Reaction to fire:  
Bfl-s1

Slip resistance:  
DS

DOP:  
1061#275BT00  
Textile Floorcovering  
EN1307



**doricx**

TÜV PROFICERT

70 710 5617-4

www.prodis.info

tested for: emissions  
harmful substances

**PREMIUM**