
























<b>CONSTRUCTION</b> Konstruktion	EN 651		Heterogeneous floor covering, cushioned with closed-cell foam
<b>COMPOUND</b> Material			Vinyl with cushioning closed cell foam backing
<b>WEARLAYER</b> Slitskikt			1K Polyurethane dispersion 2K Polyurethane laquer (optional)
<b>TOTAL THICKNESS</b> Total tjocklek	EN 428 / ISO 24346		2.00 mm
<b>WEAR LAYER THICKNESS</b> Tjocklek slitskikt	EN 429 / ISO 24340		0.225 mm
<b>TOTAL WEIGHT</b> Total vikt	EN 430 / ISO 23997		1280 g/m <sup>2</sup>
<b>ROLL SIZE</b> Rullstorlek	EN 426 / ISO 24341		400 cm x ±30 m 395 cm print width
<b>USAGE CLASSIFICATION</b> Bruksklassificering	EN 685 / ISO 10874		22+ Domestic General Use
<b>LIGHT FASTNESS</b> Ljusakthet	EN ISO 105 B02		≥ 7
<b>IMPACT NOISE REDUCTION</b> Stegljudreduktion	EN ISO 717-2		Δ L <sub>w</sub> 10 dB
<b>DIMENSIONAL STABILITY</b> Dimensionell stabilitet	EN 434 / ISO 23999		≤ 0.4 %
<b>RESIDUAL INDENTATION</b> Intrycksbeständighet	EN 433 / ISO 24343-2		≤ 0.35 mm
<b>FURNITURE LEG RESISTANCE</b> Intrycksbeständighet för möbler	EN 424 / ISO 16581		3 - No damage with foot
<b>DYNAMIC COEFFICIENT OF FRICTION</b> Dynamisk friktionskoefficient	EN 13893		> 0.3
<b>SLIP RESISTANCE</b> Halkmotstånd, ramptest	DIN 51130		R10
<b>FIRE RESISTANCE</b> Brandklassning	EN 13501-1		B <sub>f</sub> -s1
<b>THERMAL RESISTANCE</b> Värmeisolerings	ISO 8302		R=0.018m <sup>2</sup> ./W

decor  
dance  
display



			
EN 14041:2004 450 - CC0013-1			
			
Expanded (cushioned) polyvinyl chloride floorcoverings			
EN ISO 26986 / EN 653			